

AFSLUITINGEN POORTEN

NOYEZ

ZONNEBEKE 051 77 90 09

www.elkosta.com

elkosta Tracked Gate M50

Sliding gate designed to stop all threats

- certified ASTM F2656 - 07 M50/P1



The unique design of the Tracked Gate M50 affords impact protection and is therefore ideal for all critical infrastructure applications ranging from

correctional facilities, defence sites, refineries, embassies and many other designated high risk areas. The gate boasts a tracked design

with unrivalled reliability and high speed opening and closing times that are impossible to achieve with other drive principles.

AFSLUITINGEN POORTEN

NOYEZ

ZONNEBEKE 051 77 90 09

Albertstraat 21
8980 Zonnebeke
tel 051 77 90 09
fax 051 77 14 73
info@noyez.be
www.noyez.be





elkosta Tracked Gate M50 Sliding gate designed to stop all threats

The Tracked Gate M50 can be adapted in height and fitted with anti-climbing devices to comply with site-specific requirements. It can be utilised as anti vehicle barrier. The Tracked Gate M50 has been the subject of rigorous design appraisal and testing

regimes by Government agencies in the United States. It has been successfully crash tested according to ASTM F2656-07 and PAS 68. The Tracked Gate M50 system is fully compatible with all access control systems and its advanced design and technology

combined with its application flexibility, provides a total solution for all perimeter security access points vulnerable to hostile vehicle attacks.

Advantages of the elkosta Tracked Gate M50

- Up to 7000mm clear widths
- Up to 3000mm height
- Shallow foundation 400mm deep
- Top edge foundation 100 mm below finished floor level
- Certifications: ASTM F2656-07 M50/P1
PAS 68 V/7500[N3]/80/90:00/4.3 (tested with 7 m clear opening width)



We reserve the right to alter product information without any obligation.



ID:11.2.9005